

## Texnik xususiyatlari

### MYNUTE X

	25		30		35		40		
	G20		G20	G31	G20	G31	G20	G31	
Isitish rejimida nominal quvvat sarfi	20,00		25,00		30,00		30,00		kVt
Isitish rejimida nominal issiqlik ishlab chiqarish unumdorligi (80°-60° C)	19,48		24,33		29,22		29,22		kVt
Isitish rejimida nominal issiqlik ishlab chiqarish unumdorligi (50°-30° C)	21,24		26,50		32,07		32,07		kVt
Isitish rejimida minimal issiqlik quvvati	3,60	5	4,90		4,90	7	4,90	7	kVt
Isitish rejimida minimal issiqlik ishlab chiqarish unumdorligi (80°-60° C)	3,5	4,86	4,77		4,77	6,83	4,77	6,83	kVt
Isitish rejimida minimal issiqlik ishlab chiqarish unumdorligi (50°-30° C)	3,81	5,3	5,13		5,13	7,34	5,13	7,34	kVt
Issiqlik suv rejimida nominal quvvat sarfi	25,00		30,00		34,60		40,00		kVt
Issiqlik suv rejimida maksimal issiqlik ishlab chiqarish unumdorligi *	26,25		31,50		36,33		42,00		kVt
Issiqlik suv rejimida minimal issiqlik quvvati	3,60	5	4,90		4,90	7	4,90	7	kVt
Issiqlik suv rejimida minimal issiqlik ishlab chiqarish unumdorligi *	3,28	5	4,54		4,54	7	4,54	7	kVt
Maksimal nominal quvvatdagi FIK (samaradorlik) (80° -60° C)	97,4 - 97,1		97,3 - 97,4		97,3 - 97,4		97,3 - 97,4		%
30% nominal quvvatdagi FIK (samaradorlik) (30 °C qaytarish)	108,40		108,10		108,20		108,20		%
Maksimal nominal quvvatdagi FIK (samaradorlik) (50°-30° C)	106,2 - 105,8		106,0-104,7		106,9 - 104,7		106,9 - 104,7		%
Maksimal quvvat sarfi	75,00		72,00		84,00		84,00		Vt
Quvvat manbai	230-50		230-50		230-50		230-50		V/Gz
Himoya darajasi	X5D		X5D		X5D		X5D		IP
<b>Markazlashtirilgan isitish tizimi</b>									
Maksimal bosim - harorat	3-90		3-90		3-90		3-90		bar - °C
Isitish rejimida suv haroratini sozlash oralig'i	20/45 -5- 40/80		20/45540/80		20/45 540/80		20/45540/80		°C
<b>Issiqlik suv</b>									
Maksimal bosim	8,00		8,00		8,00		8,00		bar
Minimal bosim	0,15		0,15		0,15		0,15		bar
Issiqlik suv ishlab chiqarish DT = 25 °C	15,10		18,10		20,80		24,10		l/daq
Minimal issiqlik suv sarfi	2,00		2,00		2,00		2,00		l/daq
Suv haroratini sozlash oralig'i	37-60		37-60		37-60		37-60		°C
Isitish rejimida uzatish-qaytarish	3/4"		3/4"		3/4"		3/4"		Ø
Issiqlik suv kirish-chiqishi	1/2"		1/2"		1/2"		1/2"		Ø
Og'irligi	35		37		37		40		kg